



Address : 59-5,JungHeungRo73-Gil,Sari-Myeon,Goesan-Gun,ChungCheongBuk-Do,Korea. (P.C.: 367-821)
Tel : +82-(0)43-836-7672
Fax : +82-(0)43-836-7675
E-mail : uniontec@kita.net / ham@utmachine.com
Website : www.utmachine.com

Auto X-Y PU Foaming M/C(Model : UPF-2004B)



(PU SQUARE TYPE)



(PU ROUND TYPE)



TECHNICAL DESCRIPTION

- PRODUCT CAPACITY : 10~25 pcs/ min
- OUT PUT : 0.8~3.2 kg/ min
- PUMP MOTOR : 0.75 kw
- MIXING HEAD : 3200 RPM
- METERING PUMP UNIT : CHEMICAL GEAR PUMP
- TANK : TROUBLE LAYER TANK SYSTEM
- RESIN TEMP : 18~250Celsius
- ELECTRIC POWER : 380/ 220V x 3P x 50/ 60Hz
- MACHINE SIZE : W1300 x L2000 x H1500
- MACHINE WEIGHT : 2,500 kg
- TANK VOLUME : 80 LITE(FOR POLY & ISO) & 60 LITE(FOR MC)

APPLICATION

- THIS MACHINE IS DESIGNED TO MANUFACTURE AN AUTOMOTIVE AIR FILTER OF POLYURETHANE TYPE.
- ROUND/ SQUARE/ ANY SHAPE CAN BE MADE BY PLC SYSTEM.

FEATURE

- TOUCH PANNEL CONTROL SYSTEM
- AUTOMATIC WASHING SYSTEM IS INSTALLED ON THE NOZZLE
- X-Y ROBOT MOVING SYSTEM(WITH PLC PROGRAM) INSTALLED
- 2 POLY TANK(FOR YELLOW & BLACK COLOR) & 1 ISO TANK & 1 MC TANK INSTALLED

OPTIONAL PAPRT

- PU RAW MATERIAL(POLY & ISO)
- MATERIAL MIXING & LOADING PUMP
- NOZZLE & IMPELLER
- POLY & ISO CHEMICAL PUMP
- PP MOLD OR MASTER MOLD
- RUBBER HOSE
- 3 RT CHILLER(FOR COOLING & HEATING SYSTEM)
- ASSEMBLE TRANSFER CONVEYOR