



Address : 59-5,JungHeungRo73-Gil,Sari-Myeon,Goesan-Gun,ChungCheongBuk-Do,Korea. (P.C.: 367-821)
Tel : +82-(0)43-836-7672
Fax : +82-(0)43-836-7675
E-mail : uniontec@kita.net / ham@utmachine.com
Website : www.utmachine.com

Turn Table Dry Oven(Model : UTTO-20S)



TECHNICAL DESCRIPTION

- WARKING STATION & TABLE SIZE : 20 STATION & W400 x L400 X H400
- POWER SUPPLY : 220/380/415V x 50/60Hz x 35/45Kw
- TEMP. CONTROLLER : PID DIGITAL & SSR TYPE
- BLOWER MOTOR : 1.5Kw x 4PART = 6Kw
- CONVEYOR FEEDING MOTOR : 1.5Kw (INVERTER CONTROL TYPE)
- CONVEYOR BELT : SUS304 MESH BELT & 2060R CHAIN TYPE
- INSULATION : GLASS WOOL
- IN - OUT BALANCE DOOR SYSTEM
- FOOT SWITCH INSTALLED(TO MAKE TURN AFTER PP WORKING MOLD INSERT)
- MANUAL LOADING & AUTO UNLOADING SYSTEM

APPLICATION

- THIS MACHINE DESIGNED TO MAKE DRY/ HARD OF URETHANE TYPE AIR FILTER
- THE INSIDE HOTAIR WILL ROTATE STABLY & EVENLY.
- THE TEMPERATURE WILL BE CONTROLLED BY PID DIGITAL & NSSR TYPE.
- DUE TO USING OF THIS METHOD, CAN MAKE EVEN TEMPERATURE AND SAVE THE ELECTRIC EFFICIENCY.