



Address : 59-5,JungHeungRo73-Gil,Sari-Myeon,Goesan-Gun,ChungCheongBuk-Do,Korea. (P.C.: 367-821)
Tel : +82-(0)43-836-7672
Fax : +82-(0)43-836-7675
E-mail : uniontec@kita.net / ham@utmachine.com
Website : www.utmachine.com

Dry Leak Tester M/C(Model : ULT-6DL, Heavy Duty Type)





TECHNICAL DESCRIPTION

- PRODUCTION CAPACITY : 4~6 pcs/ min
- AVAILABLE TESTING OUTDIA : $\varnothing 100 \sim \varnothing 140$
- AVAILABLE TESTING HEIGHT : 150~305mm
- MAIN AIR PRESSURE : over 6kgf/ cm^2
- AIR PRESSURE : 4kgf/ cm^2
- TESTING CAPSULE : 6 CAPSULE
- MANUAL FUNCTION SYSTEM
- MAN POWER : 1
- TOTAL TESTING TIME : ONE CYCLE/ 30 sec
- LEAKAGE CHECKING RANGE : 5mmAq, over 0.5cc
- ELECTRIC POWER : 380V x 50/ 60Hz x 3P
- MACHINE SIZE : W3600 x L1300 x H2100
- MACHINE WEIGHT : 2,000 kg

APPLICATION

- THIS AUTO PRESSURE LEAK TESTER IS MANUFACTURED TO CHECK THE OIL FILTER LEAKAGE FOR AN AUTOMOBILE.
- THIS MACHINE IS AVAILABLE TO CHECKING LEAKAGE OF OIL FILTER OVER 0.5cc/ 10 sec(0.2cc ALSO CAN DETECT)BY ADOPTING HIGH QUALITY PRESSURE SENSOR. OF COURSE, THE LEAKAGE CHECKING RANGE CAN BE ADJUSTED DEPEND ON COMPANY QUALITY CONTROL LEVEL.

FEATURE

- HORIZONTAL TYPE &PLC CONTROL SYSTEM
- MANUAL LOADING &UNLOADING
- CAN CHECK RUBBER PACKING CRACK AND UNFORMED DURING TEST

OPTIONAL PART

- LINER
- THREAD LINE JIG(FOR DIFFERENT ITEM)
- CAPSULE BASE PLATE
- HEAIGHT CHANGE BAR
- PRESSURE SENSOR
- 3 WAY VALVE
- YOKOGAWA DISPLAY
- OTHER PNEUMETIC PARTS