



Address : 59-5,JungHeungRo73-Gil,Sari-Myeon,Goesan-Gun,ChungCheongBuk-Do,Korea. (P.C.: 367-821)
Tel : +82-(0)43-836-7672
Fax : +82-(0)43-836-7675
E-mail : uniontec@kita.net / ham@utmachine.com
Website : www.utmachine.com

Test Stand M/C(Model : UOST-40L)



TECHNICAL DESCRIPTION

- Flow Rate : 4~40 Liter/ min(for Passenger Type)
- Using Oil Temperature : 0°C~80°C +3°C (MAX. 100°C)
- Temp. controller : P.I.D Digital
- Heater : 220V x 3Kw
- Motor Controller : Invertor
- Prssure Gauge : 10 kgf / cm^2 x 2ea
- free and friction resistance design as a cover and oil pipe made by staneless steel.
- Machine size : 1,500x1,000x1560(WxDxH)
- 4 caster wheel installed for easy moving.
- Body Material : Staineless Steel 304

APPLICATION

- This machine designed according to JIS D -1611 &KSR 1040 oil filter test standard method perform to FILTERING EFFICIENCY TEST PRESSURE LOSS TESTING DRAIN BACK FLOW TEST RELIEF VALVE TESTING
- Contaminant &Slurry Mixer will be connected with this M/C.
- Furthermore, Centrifuge &Electric Balace Weight will be needed.

OPTIONAL PART

- Recording System