



Address : 59-5,JungHeungRo73-Gil,Sari-Myeon,Goesan-Gun,ChungCheongBuk-Do,Korea. (P.C.: 367-821)
Tel : +82-(0)43-836-7672
Fax : +82-(0)43-836-7675
E-mail : uniontec@kita.net / ham@utmachine.com
Website : www.utmachine.com

Fuel Filter Tester M/C

(Model : UFT-5L for Gasolin & UFT-10L for Diesel)



TECHNICAL DESCRIPTION

- POWER SUPPLY : 220V x 3P x 50/60Hz
- BODY MATERIAL : STAINLESS STEEL 304(PAINTING)
- FLOW METER : 0.5~5 $\frac{g}{min}$ (for Gasolin) &0.5~8 $\frac{g}{min}$ (for Diesel), DIGITAL DISPLAY
- TEM. RANGE : ~23°C (max. 30°C for Gasolin) &~ 38°C(for Diesel)
- USING OIL : KSM 2611 #5(for Gasolin) &KSM 2610 #2(for diesel)
- MOTOR CONTROL : 220V, 1HP
- TEMP. CONTROLLER : PID DIGITAL
- PRESSURE RANGE : MAX. 10Kg/ cm^2 , MIN 0.01 Kg/ cm^2
- TANK CAPACITY : 20 $\frac{g}{g}$
- BODY SIZE : W900 x L1200 x H1600

APPLICATION

- THIS M/C WAS DESIGNED FOR FUEL FILTER PRESSURE DROP &EFFICIENCY TEST IN THE LABORATORY.

OPTIONAL PAPRT

- ADDITONAL TEST JIG