



Address : 59-5,JungHeungRo73-Gil,Sari-Myeon,Goesan-Gun,ChungCheongBuk-Do,Korea. (P.C.: 367-821)
Tel : +82-(0)43-836-7672
Fax : +82-(0)43-836-7675
E-mail : uniontec@kita.net / ham@utmachine.com
Website : www.utmachine.com

Full Auto Cocking M/C(Model : UAC-40A, Passenger Type)



M/C MAIN PART



BEFORE COCKING



AFTER COCKING



MAIN COCKING PART

TECHNICAL DESCRIPTION

- ELECTRIC POWER : 380V x 50/ 60Hz x 3P
- PRODUCT CAPACITY : 35~40 pcs/ min
- COCKING TENSILE STRENGTH : 60~70 kg/cm
- SUPPLY AIR PRESSURE : 6 kg/cm
- AIR CYLINDER STROKE FOR COCKING : 100mm
- AVAILABLE SEAMING CAP THICKNESS : 0.6~0.8 mm x 4~8 point
- COCKING POWER : 5 TON+ 5 TON (HYDRAULIC SYSTEM)
- MACHINE SIZE & WEIGHT : W2000 x L2500 x H2000 / 3000 kg
- AUTO LOADING & AUTO UNLOADING & 2 SPINDLE SYSTEM (WITH MAGAZINE DEVICE)

APPLICATION

- THIS MACHINE IS DESIGNED TO MAKE A COCKING BETWEEN THE SEAMING CAP AND BOTTOM PLATE (R-PLATE).

OPTIONAL PART

- BASE HOLDING JIG (FOR BOTTOM PLATE & SEAMING CAP)
- COCKING MOLD
- COCKING PIN
- PAPER GASKET SUPPLYING DEVICE